

LATERAL LAUNCH

LISY® 4 LATERAL LAUNCH

Looking for a lateral launch system that can handle even the most challenging inspections? Look no further than the LISY 4 from IBAK. Now equipped with an electric lift system, an improved observation camera, and a quick change funnel system, the LISY 4 is one of the most user-friendly lateral launch systems available. Capable of launching from mainlines of 6" (150mm) diameter and up, and into lateral 2" (50mm) and up, the LISY 4 can truly take your lateral inspections to the next level.



Make the most out of your HD System by adding a LISY 4 Lateral Launch Attachment!

ORION-L® 3 HD/SD Camera

The LISY's articulating arm rotates and tilts with precision to place the camera in the lateral connection. Simply align the placement cone mounted on the front of the articulating arm to line up the camera to ensure quick launching!



MODULAR DESIGN

The ergonomic design and rugged construction of the LISY 4 System ensures that you will experience less breakdowns and more time in the field. This modular attachment was designed to be easy to use, simple to maintain, and safe to operate. The LISY 4 Attachment connects to your existing T76 Camera Tractor with ease so there is no need for a separate lateral launching system.



1 QUICK CHANGE FUNNEL

Our quick change funnel system is compatible with your existing funnels and also adds the option for our new aluminum funnels.

2 FUNNEL ROTATE MOTOR

The LISY 4 boasts a robust funnel rotate motor that allows operators to inspect larger diameter pipe.

3 HD OBSERVATION CAMERA

Our improved observation camera allows operators to view the position of their launch camera with clarity, in HD resolution!

4 ELECTRIC LIFT SYSTEM

Make adjustments on the fly - control the height of your system while it is underground!

5 LARGE DIAMETER

When using the Electric Lift System and the Quick Change Funnel System in conjunction, the LISY 4 can cover pipe diameters from 16" up to 78".

6 KW LISY REEL (Synchronized)

The KW LISY Synchronized reel makes launching and retrieval easy by automatically managing the pushrod cable with the mainline cable reel.

LISY 4 Technical Specifications

Pipe Diameter	6" - 78" (150mm - 1980mm) w/ accessories
Pressurized Protection	Standard
Pan Range (Articulation Arm)	180°
Tilt Range (Articulation Arm)	45°
Push Speed	Variable Control
Overall Cable Length	600' (182m)
Push Rod Length	120' (36m)